

STANDARD RIVET
Dome head

ALUMINIUM/STEEL



■ BODY: Aluminium Al Mg 3,5
■ MANDREL: Steel Zincplated A1K



UNE - EN ISO 15977

| d1 Ø mm | L Nominal mm | mm | d2 Ø mm | K mm | W Ø mm | PACKAGING | | E | | (N) | (N) | REFERENCE |
|---------------|--------------------|------|---------------|---------|--------------|-----------|-------|------|--------|-------|-------|--------------|
| | | | | | | Inner | Outer | MIN | MAX | | | |
| 2,4 | 4 | 2,50 | 5,00 | 0,60 | 1,45 | 1.000 | 8.000 | 0,5 | - 2,0 | 350 | 550 | 01010002404 |
| | 6 | | | | | 1.000 | 8.000 | 2,0 | - 4,0 | | | 01010002406 |
| | 8 | | | | | 1.000 | 8.000 | 4,0 | - 6,0 | | | 01010002408 |
| | 10 | | | | | 1.000 | 8.000 | 6,0 | - 8,0 | | | 01010002410 |
| | 12 | | | | | 1.000 | 8.000 | 8,0 | - 9,5 | | | 01010002412 |
| 3,0 | 4 | 3,10 | 6,00 | 1,00 | 1,80 | 500 | 4.000 | 0,5 | - 1,5 | 550 | 850 | 01010003004 |
| | 5 | | | | | 500 | 4.000 | 0,5 | - 2,5 | | | 01010003005 |
| | 6 | | | | | 500 | 4.000 | 1,5 | - 3,5 | | | 01010003006 |
| | 7 | | | | | 500 | 4.000 | 1,5 | - 4,5 | | | 01010003007 |
| | 8 | | | | | 500 | 4.000 | 3,5 | - 5,0 | | | 01010003008 |
| | 9 | | | | | 500 | 4.000 | 5,5 | - 6,0 | | | 01010003009 |
| | 10 | | | | | 500 | 4.000 | 5,0 | - 7,0 | | | 01010003010 |
| | 12 | | | | | 500 | 4.000 | 7,0 | - 9,0 | | | 01010003012 |
| | 14 | | | | | 500 | 4.000 | 9,0 | - 11,0 | | | 01010003014 |
| | 16 | | | | | 500 | 4.000 | 11,0 | - 13,0 | | | 01010003016 |
| | 18 | | | | | 500 | 4.000 | 13,0 | - 15,0 | | | 01010003018 |
| 3,2 | 4 | 3,30 | 6,40 | 1,00 | 1,80 | 500 | 4.000 | 0,5 | - 2,5 | 750 | 1.100 | 01010003204 |
| | 5 | | | | | 500 | 4.000 | 0,5 | - 2,5 | | | 01010003205 |
| | 6 | | | | | 500 | 4.000 | 1,5 | - 3,5 | | | 01010003206 |
| | 8 | | | | | 500 | 4.000 | 3,5 | - 5,0 | | | 01010003208 |
| | 10 | | | | | 500 | 4.000 | 5,0 | - 7,0 | | | 01010003210 |
| | 12 | | | | | 500 | 4.000 | 7,0 | - 9,0 | | | 01010003212 |
| | 15 | | | | | 500 | 4.000 | 9,0 | - 12,0 | | | 01010003215 |
| | 18 | | | | | 500 | 4.000 | 12,0 | - 15,0 | | | 01010003218 |
| | 20 | | | | | 500 | 4.000 | 15,0 | - 18,0 | | | 01010003220 |
| 4,0 | 5 | 4,10 | 8,00 | 1,40 | 2,20 | 500 | 4.000 | 0,5 | - 2,5 | 1.250 | 1.800 | 01010004005 |
| | 6 | | | | | 500 | 4.000 | 1,0 | - 3,0 | | | 01010004006 |
| | 7 | | | | | 500 | 4.000 | 3,0 | - 4,5 | | | 01010004007 |
| | 8 | | | | | 500 | 4.000 | 3,0 | - 5,0 | | | 01010004008 |
| | 10 | | | | | 500 | 4.000 | 5,0 | - 6,5 | | | 01010004010 |
| | 12 | | | | | 500 | 3.000 | 6,5 | - 8,5 | | | 01010004012 |
| | 14 | | | | | 500 | 3.000 | 8,5 | - 10,5 | | | 01010004014 |
| | 16 | | | | | 500 | 3.000 | 10,5 | - 12,5 | | | 01010004016 |
| | 18 | | | | | 500 | 3.000 | 12,5 | - 14,5 | | | 01010004018 |
| | 20 | | | | | 500 | 3.000 | 14,5 | - 16,5 | | | 01010004020 |
| | 25 | | | | | 250 | 1.500 | 16,5 | - 21,5 | | | 01010004025 |
| | 30 | | | | | 250 | 1.500 | 21,5 | - 26,0 | | | 01010004030 |
| | 35 | | | | | 250 | 1.500 | 26,0 | - 31,0 | | | 01010004035 |
| | 40 | | | | | 250 | 1.500 | 31,0 | - 36,0 | | | 01010004040 |
| 4,8 | 6 | 4,90 | 9,50 | 1,50 | 2,65 | 500 | 3.000 | 0,5 | - 3,0 | 1.850 | 2.600 | 01010004806 |
| | 8 | | | | | 500 | 3.000 | 3,0 | - 4,5 | | | 01010004808 |
| | 10 | | | | | 500 | 3.000 | 4,5 | - 6,0 | | | 01010004810 |
| | 12 | | | | | 500 | 3.000 | 6,0 | - 8,0 | | | 01010004812 |
| | 14 | | | | | 250 | 2.000 | 8,0 | - 10,0 | | | 01010004814 |
| | 16 | | | | | 250 | 2.000 | 10,0 | - 12,0 | | | 01010004816 |
| | 18 | | | | | 250 | 1.500 | 12,0 | - 14,0 | | | 01010004818 |
| | 21 | | | | | 250 | 1.500 | 14,0 | - 17,0 | | | 01010004821 |
| | 24 | | | | | 200 | 1.200 | 17,0 | - 20,0 | | | 01010004824 |
| | 27 | | | | | 200 | 1.200 | 20,0 | - 23,0 | | | 01010004827 |
| | 30 | | | | | 200 | 1.200 | 23,0 | - 25,0 | | | 01010004830 |
| | 32 | | | | | 200 | 1.200 | 25,0 | - 27,0 | | | 01010004832 |
| | 35 | | | | | 200 | 1.200 | 27,0 | - 30,0 | | | 010100048352 |
| | 40 | | | | | 150 | 900 | 30,0 | - 35,0 | | | 01010004840 |
| | 45 | | | | | 100 | 600 | 35,0 | - 40,0 | | | 01010004845 |
| | 50 | | | | | 100 | 600 | 40,0 | - 45,0 | | | 01010004850 |


Tests according to EN ISO 14589

ALUMINIUM/STEEL

STANDARD RIVET
Dome head



■ BODY: Aluminium Al Mg 3,5
■ MANDREL: Steel Zincplated A1K



UNE - EN ISO 15977

| d1 Ø mm | L Nominal mm | mm | d2 Ø mm | K mm | W Ø mm | PACKAGING | | E | | (N) | (N) | REFERENCE |
|---------------|--------------------|------|---------------|---------|--------------|-----------|-------|--------|--------|-------|-------|-------------|
| | | | | | | Inner | Outer | MIN | MAX | | | |
| 5,0 | 6 | 5,10 | 9,50 | 1,60 | 2,65 | 500 | 3.000 | 0,5 | - 3,0 | 2.150 | 3.100 | 01010005006 |
| | 8 | | | | | 500 | 3.000 | 3,0 | - 4,5 | | | 01010005008 |
| | 10 | | | | | 500 | 3.000 | 4,5 | - 6,0 | | | 01010005010 |
| | 12 | | | | | 500 | 3.000 | 6,0 | - 8,0 | | | 01010005012 |
| | 14 | | | | | 250 | 2.000 | 8,0 | - 10,0 | | | 01010005014 |
| | 16 | | | | | 250 | 2.000 | 10,0 | - 12,0 | | | 01010005016 |
| | 18 | | | | | 250 | 1.500 | 12,0 | - 14,0 | | | 01010005018 |
| | 20 | | | | | 250 | 1.500 | 14,0 | - 16,0 | | | 01010005020 |
| | 25 | | | | | 200 | 1.200 | 16,0 | - 21,0 | | | 01010005025 |
| | 30 | | | | | 200 | 1.200 | 21,0 | - 25,0 | | | 01010005030 |
| | 35 | | | | | 150 | 900 | 27,0 | - 30,0 | | | 01010005035 |
| | 40 | | | | | 150 | 900 | 30,0 | - 35,0 | | | 01010005040 |
| | 45 | | | | | 100 | 600 | 35,0 | - 40,0 | | | 01010005045 |
| | 50 | | | | | 100 | 600 | 40,0 | - 45,0 | | | 01010005050 |
| 6,0 | 8 | 6,10 | 12,00 | 1,80 | 3,20 | 250 | 1.500 | 2,0 | - 3,0 | 3.200 | 4.600 | 01010006008 |
| | 10 | | | | | 250 | 1.500 | 3,0 | - 5,0 | | | 01010006010 |
| | 12 | | | | | 250 | 1.500 | 5,0 | - 7,0 | | | 01010006012 |
| | 14 | | | | | 250 | 1.500 | 7,0 | - 9,0 | | | 01010006014 |
| | 16 | | | | | 250 | 1.500 | 9,0 | - 11,0 | | | 01010006016 |
| | 18 | | | | | 200 | 1.200 | 11,0 | - 13,0 | | | 01010006018 |
| | 20 | | | | | 200 | 1.200 | 13,0 | - 15,0 | | | 01010006020 |
| | 25 | | | | | 200 | 1.200 | 15,0 | - 20,0 | | | 01010006025 |
| | 30 | | | | | 150 | 900 | 20,0 | - 25,0 | | | 01010006030 |
| | 35 | | | | | 100 | 600 | 25,0 | - 30,0 | | | 01010006035 |
| 6,4 | 12 | 6,50 | 13,00 | 2,20 | 3,60 | 250 | 1.500 | 3,0 | - 6,0 | 3.400 | 4.850 | 01010006412 |
| | 15 | | | | | 250 | 1.500 | 6,0 | - 9,0 | | | 01010006415 |
| | 18 | | | | | 200 | 1.200 | 9,0 | - 12,0 | | | 01010006418 |
| | 22 | | | | | 200 | 1.200 | 12,0 | - 16,0 | | | 01010006422 |
| | 26 | | | | | 150 | 900 | 16,0 | - 20,0 | | | 01010006426 |
| | 30 | | | | | 150 | 900 | 20,0 | - 22,0 | | | 01010006430 |
| | 35 | | | | | 100 | 600 | 24,0 | - 29,0 | | | 01010006435 |
| | 40 | | | | | 500 | 29,0 | - 34,0 | | | | G1010006440 |
| | 50 | | | | | 500 | 29,0 | - 42,0 | | | | 01010006450 |
| 7,8 | 15 | 8,00 | 13,50 | 2,20 | 3,60 | 1.000 | 6,0 | - 9,0 | 5.000 | 7.500 | | G1010007815 |
| | 22 | | | | | 1.000 | 9,0 | - 16,0 | | | | G1010007822 |

Tests according to EN ISO 14589